

BT Levio

LWE180

LWE200

LWE250



Pedestrian Lowlifter

BT Levio

Specification for lowlifter trucks						LWE180	LWE200	LWE250
Identification	1.1	Manufacturer				BT	BT	BT
	1.2	Model				LWE180	LWE200	LWE250
	1.3	Drive				Electric	Electric	Electric
	1.4	Operator type				Pedestrian	Pedestrian	Pedestrian
	1.5	Load capacity/rated load	Q	kg		1800	2000	2500
	1.6	Load centre	c	mm		600	600	600
	1.7	Load distance, centre of support arm wheel to face of forks	x	mm		898	898	898
	1.8	Wheelbase	y	mm		1287	1287	1287
	Weight	2.1	Service weight including battery		kg		554	554
2.2		Axle load, with load, drive/castor/fork wheel		kg		760/150/1435	815/150/1580	950/150/1945
2.3		Axle load, without load, drive/castor/fork wheel		kg		260/150/135	260/150/135	260/150/135
Wheels	3.1	Drive/castor/fork wheel			Tophane/Tophane/PUR *)			Vulkollan/Topthane/Vulkollan *)
	3.2	Wheel size, front		mm	Ø230x70	Ø230x70	Ø230x70	
	3.3	Wheel size, rear		mm	Ø85x75	Ø85x75	Ø85x75	
	3.4	Additional wheels (dimensions)		mm	Ø125x50	Ø125x50	Ø125x50	
	3.5	Wheels, number front/rear (x=driven wheels)			1x+2/4	1x+2/4	1x+2/4	
	3.6	Track width, front	b ₁₀	mm	430	430	430	
	3.7	Track width, rear	b ₁₁	mm	370	370	370	
Dimensions	4.4	Lift	h ₃	mm	120	120	120	
		Lift height	h ₂₃	mm	205	205	205	
	4.8	Stand height (optional platform)	h ₇	mm	—	150	—	
	4.9	Height of tiller in drive position, min./max.	h ₁₄	mm	865/1235	865/1235	865/1235	
	4.15	Height, fork lowered	h ₁₃	mm	85	85	85	
	4.19	Overall length	l ₁	mm	1688	1688	1688	
	4.20	Length to face of forks	l ₂	mm	538	538	538	
	4.21	Overall width	b ₁	mm	726	726	726	
	4.22	Fork dimensions	s/e/l	mm	78/180/1150 *)	78/180/1150 *)	78/180/1150 *)	
	4.25	Width over forks	b ₅	mm	550 *)	550 *)	550 *)	
	4.32	Ground clearance, centre of wheelbase	m ₂	mm	21	21	21	
	Performance data	5.1	Travel speed, with/without load		km/h	6/6	6/6	6/6
5.2		Lift speed, with/without load		m/s	0.04/0.05	0.06/0.09	0.05/0.09	
5.3		Lowering speed, with/without load		m/s	0.09/0.08	0.09/0.08	0.09/0.08	
5.8		Max. gradeability, with/without load ²⁾		%	9/18 ¹⁾	9/18 ¹⁾	8/18 ¹⁾	
5.10		Service brake			Electromagnetic	Electromagnetic	Electromagnetic	
Electric motor		6.1	Drive motor rating S2 60 min		kW	1.0	1.5	1.5
		6.2	Lift motor rating at S3 15%		kW	1.0 ²⁾	1.4 ²⁾	1.4 ²⁾
	6.4	Battery voltage/nominal capacity K _s		V/Ah	24/225 *)	24/225 *)	24/225 *)	
	6.5	Battery weight		kg	214 *)	214 *)	214 *)	
Others	8.1	Type of drive control			BT Powerdrive	BT Powerdrive	BT Powerdrive	

¹⁾ Measured according to company standard

²⁾ S3 10%

*) Further alternatives are available and will produce other values.

Data is based on standard configurations: Medium battery compartment.

Truck performance and dimensions are nominal and subject to tolerances.
BT Products AB products and specifications are subject to change without notice.

